

SAFETY DATA SHEET

1. Identification

Product identifier Flosan Z10-90

Recommended use For Industrial Use Only

Recommended restrictions Users should be informed of the potential presence of

respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as

required under applicable regulations.

Manufacturer/Supplier information

Company name: FRC Global

Address: 1000 N. West St.

Suite 1200 #3008 Wilmington, DE 19801

Product Support/Technical Services

Phone: (514) 931-5711

Website www.FRCglobal.com

Emergency telephone number: Corporate Office: (514) 931-5711

Technical Services: (514) 931-5711

Contact E-Mail: <u>LadleDr@FRCglobal.com</u>

2. Hazard(s) identification

Physical hazards Skin Irrit. 2 Causes skin irritation.

Eye Irrit. 2A Causes serious eye irritation. STOT SE 3 May cause respiratory irritation.

Heath hazards Category 1A Carcinogenicity

Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements





Signal word Danger, Warning.

Hazard Statement H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H350 May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until

all safety precautions have been read and understood.

MATERIAL NAME: FLOSAN Z10-90

Wear protective gloves/protective clothing/eye

protection. Do not get in the eyes, on skin, or on clothing. If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present, and easy to do.

Continue rinsing.

IF INHALED: Remove the person to fresh air and keep

comfortable for breathing.

If concerned: Get medical advice/attention.

Storage Store in a well-ventilated place. Keep the container tightly

closed.

Disposal Dispose of contents/container in accordance with

local/regional/national/international regulations

Hazard(s) not otherwise Classified (HNOC)

None Known.

Supplemental information

Response

Users should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica (quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

Individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance.

in accordance

3. Composition/information on ingredients

Chemical Name	Common Name/Synonyms	CAS Number	%
Chromium (III) oxide		1308-38-9	*
Magnesium Oxide		1309-48-4	*
Aluminum Oxide (Non-Fibrous)		1344-28-1	*
Silica		14808-60-7	*
Carbon		1333-86-4	*
Iron Oxide		1309-37-1	*
Zirconium silicate		10101-52-7	*

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or

persist.

Skin contact Avoid contact with skin. Wash off with soap and water.

Get medical attention if irritation develops and persists.

MATERIAL NAME: FLOSAN Z10-90

Eye contact Avoid contact with eyes. Rinse with water. Get medical

attention if irritation develops and persists.

Ingestion Unlikely route of exposure. If ingested in sufficient quantity

and the victim is conscious, give 1-2 glasses of water. Never give anything by mouth to an unconscious person. Leave the decision to induce vomiting to qualified medical personnel, since particles may be aspirated into the lungs.

Seek immediate medical attention.

Most important symptoms/effects, acute and delayed

Direct contact with the eyes may cause temporary

irritation. Coughing.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep the victim under observation.

Symptoms may be delayed.

General information If concerned: Get medical advice. Ensure that medical

personnel are aware of the material(s) involved and take

precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Use fire-extinguishing media appropriate for surrounding

materials.

Unsuitable extinguishing media

Not available.

Specific hazards arising from the chemical

Not available.

Special protective equipment and precautions for firefighters

Wet material should be kept out of eyes and off skin in any

fire, and wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. The material does not give off

tania famora in a financial as it is made a

toxic fumes in a fire unless it is molten.

6. Accidental release measures

Personal precautions, protective equipment, and emergency procedures

Keep unnecessary personnel away. Keep people away from, and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Use a NIOSH/MSHA-approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material if this is without risk. Collect dust using a vacuum cleaner equipped with a HEPA filter.

MATERIAL NAME: FLOSAN Z10-90

Large Spills: Wet down with water and dike for later disposal. Shovel the material into a waste container. Avoid the generation of dust during clean-up. Following product recovery, flush the area with water.

Small Spills: Sweep up or vacuum up spillage and collect it in a suitable container for disposal. For waste disposal, see

section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses, or onto the around.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep the formation of airborne dust to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in the original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limit

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Chromium (III) oxide	PEL	0.5 mg/m3	
(CAS 1308-38-90)			
Aluminum Oxide (Non-Fibrous)	PEL	5 mg/m3	Respirable fraction
(CAS 1344-28-1)			
Magnesium Oxide	PEL	15 mg/m3	Total particulate.
(CAS 1309-48-4)			
Carbon	PEL	3.5 mg/m3	
(CAS 1333-86-4)			
(CAS 1333-86-4) US. OSHA Table Z-3 (29 CFR 19 Components	10.1000) Type	Value	Form
US. OSHA Table Z-3 (29 CFR 19	•	Value 0.3 mg/m3	Form Total dust.
US. OSHA Table Z-3 (29 CFR 19 Components	Туре		
US. OSHA Table Z-3 (29 CFR 19 Components Quartz (SiO2)	Туре	0.3 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 19 Components Quartz (SiO2)	Type TWA	0.3 mg/m3 0.1 mg/m3	Total dust. Respirable.
US. OSHA Table Z-3 (29 CFR 19 Components Quartz (SiO2) (CAS 14808-60-7)	Type TWA	0.3 mg/m3 0.1 mg/m3	Total dust. Respirable.
US. OSHA Table Z-3 (29 CFR 19 Components Quartz (SiO2) (CAS 14808-60-7) US. ACGIH Threshold Limit Value	Type TWA	0.3 mg/m3 0.1 mg/m3 2.4 mppcf	Total dust. Respirable. Respirable.

MATERIAL NAME: FLOSAN Z10-90

(CAS 1309-48-4)		10 1119/1110	milatable macrom.
Aluminum Oxide (Non-Fibrous) (CAS1344-28-1)	TWA	1 mg/m3	Respirable fraction.
Carbon (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Chemical Ha	azards Type	Value	Form
US. NIOSH: Pocket Guide to Chemical Harmonents Chromium (III) oxide (CAS 1308-38-90)		Value 0.5 mg/m3	Form
Components Chromium (III) oxide	Туре		Form

Biological limit values No biological exposure limits were noted for the

ingredient(s).

TWA

Exposure guidelines Occupational exposure to nuisance dust (total and

respirable) and respirable crystalline silica should be

10 ma/m3

Inhalable fraction.

monitored and controlled.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Magnesium Oxide

(CAS 14808-60-7)

Hand protection Wear appropriate chemical-resistant gloves.

Other Wear suitable protective clothing. Use of an impervious

apron is recommended.

Respiratory protection Use a NIOSH/MSHA-approved respirator if there is a risk of

exposure to dust/fume at levels exceeding the exposure

limits.

Thermal hazards Wear appropriate thermal protective clothing, when

necessary









General Hygiene Considerations

MATERIAL NAME: FLOSAN Z10-90

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.

Form Solid Powder. Color Not available. Odor Not available. Odor threshold Not available. На Not available. Melting point/freezing point Not available.

Initial boiling point and boiling range

Not available. Flash point Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower (%)

Not available.

Flammability limit - upper (%)

Not available.

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure Not available. Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water)

Not available. Not available.

Auto-ignition temperature Decomposition temperature Not available. Viscosity Not available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal

conditions of use, storage, and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions

No dangerous reaction is known under conditions of

normal use.

Conditions to avoid Contact with incompatible materials. Refractories

containing crystalline silica may, after service, contain

MATERIAL NAME: FLOSAN Z10-90

more or less crystalline silica. Care must be taken to avoid and/or control dust from demolition. If in doubt of the

proper protection, seek advice from a safety professional. Strong oxidizing agents. Chlorine. Incompatibility is based

strictly upon potential theoretical reactions between chemicals and may not be specific to industrial application

exposure. Contact your sales representative for

clarification.

Hazardous decomposition products

Incompatible materials

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Dust may irritate the respiratory system. Prolonged

inhalation may be harmful.

Skin contact Dust or powder may irritate the skin.

Eye contact Dust may irritate the eyes.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical, and toxicological characteristics:

Dust may irritate the respiratory tract, skin, and eyes.

Coughing.

Information on toxicological effects

Acute toxicity Not available.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation

Direct contact with the eyes may cause temporary

irritation.

Respiratory or skin sensitization

Respiratory sensitization

Not a respiratory sensitizer.

Skill selisitization

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data is available to indicate product, or any

components present at greater than 0.1% are mutagenic or

genotoxic.

Carcinogenicity In 1997, IARC (the International Agency for Research on

Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However, in making the overall evaluation, IARC noted that

"carcinogenicity was not detected in all industrial

circumstances studied. Carcinogenicity may be dependent

on inherent characteristics of the crystalline silica or external factors affecting its biological activity or

distribution of its polymorphs." (IARC Monographs on the

evaluation of the carcinogenic risks of chemicals to humans, Silica, silicate dust, and organic fibers, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation

MATERIAL NAME: FLOSAN Z10-90

of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry).

Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

According to the current state of the art, worker

protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled. This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon (CAS 1333-86-4) 2B Possibly carcinogenic to humans. Chromium (III) oxide (CAS 1308-38-9) 3 Not classifiable as to carcinogenicity

to humans.

Quartz (SiO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

US National Toxicology Program (NTP) Report on Carcinogens

Quartz (SiO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

US OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or

developmental effects.

Specific target organ toxicity - single exposure

Not classified.

Specific target organ toxicity - repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure

may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous.

However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on

the environment.

Persistence and degradability

No data is available on the degradability of this product.

Bio-accumulative potential

No data available.

Mobility in soil
Other adverse effects

No other adverse environmental effects (e.g. ozone

depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are

expected from this component.

13. Disposal considerations

MATERIAL NAME: FLOSAN Z10-90

Disposal instructionsThis product, in its present state, when discarded or

disposed of, is not hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA

criteria for hazardous waste.

Hazardous waste code Since this product is used in several industries, no Waste

Code can be provided by the supplier. The Waste Code should be determined in arrangement with your waste

disposal partner or the responsible authority.

Waste from residues / unused products

Not available.

Contaminated packaging Not available.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as

defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. One or more components are not listed on TSCA. All chemical substances in this product are listed on the TSCA chemical substance inventory where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Chemical

Not listed.

MATERIAL NAME: FLOSAN Z10-90

SARA 313 (TRI reporting)

Chemical Name	CAS number	% by wt.
Chromium (III) oxide	1308-38-9 40	*
Aluminum Oxide (Non-Fibrous)	1344-28-1	*

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Chromium (III) oxide (CAS 1308-38-9)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR

68.130) Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

US California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US Massachusetts RTK - Substance List

Aluminum Oxide (Non-Fibrous) (CAS 1344-28-1)

Magnesium Oxide (CAS 1309-48-4)

Carbon (CAS 1333-86-4)

Chromium (III) oxide (CAS 1308-38-9)

Quartz (SiO2) (CAS 14808-60-7)

US New Jersey Worker and Community Right-to-Know Act

Aluminum Oxide (Non-Fibrous) (CAS 1344-28-1)

Magnesium Oxide (CAS 1309-48-4)

Carbon (CAS 1333-86-4)

Chromium (III) oxide (CAS 1308-38-9)

Quartz (SiO2) (CAS 14808-60-7)

US Pennsylvania Worker and Community Right-to-Know Law

Aluminum Oxide (Non-Fibrous) (CAS 1344-28-1)

Magnesium Oxide (CAS 1309-48-4)

Carbon (CAS 1333-86-4)

Quartz (SiO2) (CAS 14808-60-7)

US Rhode Island RTK Aluminum Oxide (Non-Fibrous) (CAS 1344-28-1)

US California Proposition 65

WARNING: This product contains a chemical known to the

State of California to cause cancer.

US California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon (CAS 1333-86-4) Listed: February 21, 2003 Quartz (SiO2) (CAS 14808-60-7) Listed: October 1, 1988

16. Other information, including date of preparation or last revision

This information is supplied to be informative and to alert the user of the material. The ultimate compliance with federal, state, and/or local regulations concerning the use of this material, or compliance with respect to product liability, rests solely upon the purchaser thereof.

Prepared by: FRC Global

MATERIAL NAME: FLOSAN Z10-90

Date: October 2020

DISCLAIMER: Reasonable care has been taken in the preparation of the information provided and believed to be correct as of the issue date. However, FRC Global makes no representation or warranties and assumes no responsibility as to the completeness and accuracy thereof. Users must make their own determination as to the suitability of the product for their purpose before use. FRC Global will not be responsible for any damages of any nature directly or indirectly whatsoever resulting from the use of, reliance upon, or misuse of the information contained herein.

End of Safety Data Sheet

MATERIAL NAME: FLOSAN Z10-90